



10/2021

# **Mod: N65/R212G-P9**

**Production code: 11121701-0-N-K**

Model :	N65/R212G-P9	N65/R316G-P9
		
Description	2x GN2/3 Under Broiler Refrigerator Counter Diamond, Feet H95/155, R290	3x GN2/3 Under Broiler Refrigerator Counter Diamond, R290, Stainless steel back
Light	no	no
Key lock	no	no
Range (°C)	-2 +8	-2 +8
Operating Mode	Ventilated	Ventilated
<b>External Dimensions</b>		
Width (mm)	1200	1600
Depth/with open drawers (mm)	600 / 1195	600 / 1195
Worktop height (mm)	645-705	645-705
<b>Internal Dimensions</b>		
Width (mm)	780	1215
Depth (mm)	475	475
Height (mm)	410	410
Gross capacity (L)	152	237
<b>Defrost</b>		
Type of defrost	Automatic by time, stop compressor	Automatic by time, stop compressor
No. of defrost in 24h	4	4
Evaporation of defrost water	Hot gas	Hot gas
<b>Compressor</b>		
Brand	Huayi / Cubigel	Huayi / Cubigel
Model	NLY45RA_b	GLY45RA_b
Power (hp)	1/5	1/6
Cooling power (W)	357	220
Evaporation temp. / Condensation temp. (°C)	-10 / +45	-10 / +45
Climate class (Temp./RH)	5 (40°C - 40%)	5 (40°C - 40%)
<b>Refrigerant</b>		
Refrigerant fluid / GWP	R290 / 3	R290 / 3
Refrigerant charge (kg)	0,075	0,075
<b>Electronic Controller</b>		
Brand	Dixell	Dixell
Model	XR30CH	XR30CH
<b>Electrical</b>		
Power input (W/A)	177 / 0,87	177 / 0,87
Power supply (V/Hz)	220-240/50	220-240/50
220V/60Hz	no	no
<b>Packaging details</b>		
Packed volume (m³)	0,73	0,98
Gross weight (kg)	100	160
Net weight (kg)	85	145
<b>Efficiency Information</b>		
Energy efficiency class	B	C
Daily Energy Consumption (E24h) (kWh)	1,50	2,20
Annual Energy Consumption (AEC) (kWh)	548	803
Net volume (L)	106	159
Climate class	4	4